

Description: Extra light weight bead rolled flock lined natural rubber gloves

- Features & Benefits:
- \* Anatomically shaped for comfort
  - \* Anti-slip pattern for good grip in wet and dry conditions
  - \* Beaded cuff to improve tear resistance during donning and removal and help prevent droplets from travelling beyond the glove length
  - \* Improved sensitivity and dexterity
  - \* Natural rubber
  - \* Pure cotton lining to absorb perspiration
  - \* Compliant with (EC) 1935:2004 and EU 10/2011 and BfR XXI standards

Applications: Agriculture, Chemical Industry, Food Industry, Pharmaceutical, Facility maintenance

Elastomer: Natural rubber

Thickness: 0.38 +/- 0.04 mm

Lining: Flocklined

Former: Honeycomb CIH

Exterior: Finished smooth

Cuff Types: Bead rolled

Treatments: Un-chlorinated

Colours: Blue B1, Blue B2, Pink P2, Yellow Y1

AQL: 1.00



CE Certification: Conforms to PPE Regulation EU 2016/425 to (Complex Design) Personal Protective Equipment after assessment against standards EN 374-1:2016+A1:2018, EN 374-5:2016, EN 388:2016+A1:2018 and EN 420:2003+A1:2009

Conforms to: ASTM D4679 of 2002

Physical Dimensions:	Size	Palm	Wrist	Cuff	Length
	6-6.5	194	180	244	300
	7-7.5	204	183	245	300
	8-8.5	212	196	260	300
	9-9.5	230	221	279	300
	XL	245	230	290	300

Circumference in mm, +/- 5 mm      Tol. +/- 5 mm

Shelf Life 1 Years


EN 374-4

#### Protection against Chemical hazards

Performance

Degradation %

EN ISO 374-1/TYPE A



- \* Methanol (A)
- \* Sodium hydroxide 40% (K)
- \* Sulphuric acid 96% (L)
- \* Nitric acid 65% (M)
- \* Acetic acid 99% (N)
- \* Hydrogen peroxide 30% (P)
- \* Formaldehyde 37% (T)
- \* Hydrofluoric acid 40% (S)

Level 1	22.3
Level 6	-26.8
Level 2	49.8
Level 4	24.7
Level 1	27.7
Level 4	-16.9
Level 6	-16.5
Level 5	X

Note: Printed copies are valid only on the date printed

Printed Date: 04-Jan-2022

Revision:3

Published Date: 17-Jun-2020

**DPL**  
Handling you with care

No: 400, Deans Road, Colombo 10, Sri Lanka

Phone: +94-0122-683-964

Fax: +94-0122-699-018

E-Mail: postmast@dplgroup.com

Protection against Mechanical hazards		Performance
---------------------------------------	--	-------------

EN 388



- \* Abrasion resistance
- \* Blade cut resistance
- \* Tear resistance
- \* Puncture resistance
- \* TDM cut resistance

Level 1  
Level 0  
Level 1  
Level 0  
X

Protection against Micro-organisms risk		Performance
---	--	-------------

EN ISO 374-5



- \* Protection against bacteria and fungi
- \* Protection against viruses

Pass  
Not tested