

Description: Flock lined nitrile gloves, 15mil

- Features & Benefits:
- * Anti-slip pattern for good grip in wet and dry conditions
 - * Manufactured under a stringent quality management system
 - * Nitrile rubber for solvent resistance
 - * Outstanding abrasion resistance
 - * Straight cuff
 - * Biodegradable

Applications: Aircraft Industry, Automobile Industry, Chemical Industry, Petrochemical Industry

Elastomer: Nitrile rubber

Thickness: 0.38 +/- 0.05 mm

Lining: Flocklined

Former: Reverse Lozenge, CVIL

Exterior: Chlorinated

Cuff Types: Straight

Treatments: Chlorinated/Unchlorinated

Colours: Blue B14, Green G8, Red R8, Yellow Y2, Green 40

AQL: 1.00



CE Certification: Conforms to PPE Regulation EU 2016/425 to (Complex Design) Personal Protective Equipment after assessment against standards EN 374-1:2016+A1:2018, EN 374-5:2016, EN 388:2016+A1:2018 and EN 420:2003+A1:2009

Conforms to: ASTM D4679 of 2002

Physical Dimensions:	Size	Palm	Wrist	Cuff	Length
	6	195	185	284	330
	7	214	206	296	330
	8	220	218	302	330
	9	244	234	310	330
	10	268	256	326	330
	11	278	268	330	330

Circumference in mm, +/- 10 mm Tol. +/- 10 mm

Shelf Life 1 Years

EN 374-4

Protection against Chemical hazards

Performance

Degradation %

EN ISO 374-1/TYP A



* Methanol (A)	Level 2	70.1
* Toluene (F)	Level 1	81.8
* n-Heptane (J)	Level 6	0
* Sodium hydroxide 40% (K)	Level 6	4.5
* Sulphuric acid 96% (L)	Level 3	61.9
* Nitric acid 65% (M)	Level 2	98.7
* Acetic acid 99% (N)	Level 3	91.9
* Ammonium hydroxide 25% (O)	Level 6	-5.8
* Hydrogen peroxide 30% (P)	Level 6	-11.7
* Formaldehyde 37% (T)	Level 6	-15.6

Note: Printed copies are valid only on the date printed

Printed Date: 04-Jan-2022

Revision:14

Published Date: 20-Nov-2021

DPL
Handling you with care

No: 400, Deans Road, Colombo 10, Sri Lanka

Phone: +94-0122-683-964

Fax: +94-0122-699-018

E-Mail: postmast@dplgroup.com

Protection against Mechanical hazards **Performance**

EN 388:2016



- * Abrasion resistance
- * Blade cut resistance
- * Tear resistance
- * Puncture resistance
- * TDM cut resistance

Level 4
Level 1
Level 0
Level 1
X

Protection against Micro-organisms risk **Performance**

EN ISO 374-5



- * Protection against bacteria and fungi
- * Protection against viruses

Pass
n/a