

CODE: MBK17-060AF-VR

ERP: 0135445

## Fire Extinguisher 6L Foam (BSI KITEMARK) BSI KITEMARK SERIES

Fire Extinguisher 6L with One Seam Vessel with INTERNAL PLASTIC LAYER.

**METALLIC BRACKET INCLUDED**

[FIRE EXTINGUISHERS USER INSTRUCTIONS](#)



### CHARACTERISTICS

Approval Type	BSI, GTC, MED, MPA DRESDEN, NCP - KIWA
Extinguisher Type	Portable
Pressure Type	Stored Pressure
Suppression Agent Type	Foam
Capacity	6L
Extinguishing Agent	FOAM
Operating temperature	+5 to +60 °C
Max Allowable Pressure	17 bar
Max Working Pressure	30 bar
Volume of Equipment	7,8 L
Cylinder Height	469±2 mm
Cylinder Diameter	162±2 mm
Cylinder Neck Thread	M30x1.5
Cylinder Material	DC01
Valve Material	CuZn40Pb2
Safety Valve	22-27 bar
Approx. gross Weight	10 kg
Approx. Dimensions	564x162 mm
Paint Finish	RAL 3000



Issue Date: 14/11/2024

Information may change

**HEADQUARTERS:** KATHIANA AKROTIRIOU P.C. 73100 CHANIA, CRETE - GREECE, TEL.: +30 28210 63222, FAX :+30 28210 91644

**ATHENS DISTRIBUTION CENTER:** SHINEZA - ASPROPIRGOS, P.C. 19300, ATTICA - GREECE, TEL.: +30 210 4614006, FAX: +30 210 5595986

**NORTH GREECE DISTRIBUTION CENTER:** 8 ARKADIOU str. KALOCHORI - THESSALONIKI, P.C. 57009, TEL.: +30 2310 785668, FAX: +30 2310 574793

**CENTRAL & EAST CRETE DISTRIBUTION CENTER:** P<sup>1</sup> str. INDUSTRIAL ZONE OF HERAKLION - CRETE - GREECE, P.C. 71601, TEL/ FAX: +30 2810 333151

[www.mobiakfire.com](http://www.mobiakfire.com)