

CODE: MBK14-500AF-W1A

ERP: 0135336

Trolley Fire Extinguisher 50Lt Foam BSI KITEMARK SERIES

50Lt Trolley Fire Extinguisher with 5m Discharge Hose. Pressure Gauge Safety Release Valve.

[FIRE EXTINGUISHERS USER INSTRUCTIONS](#)



CHARACTERISTICS

Approval Type	BSI
Extinguisher Type	Trolley
Pressure Type	Stored Pressure
Suppression Agent Type	Foam
Capacity	50Lt
Extinguishing Agent	3%
Operating Temperature	+5°C to +60° °C
Max Allowable Pressure	18 bar
Test Pressure	35 bar
Volume of Equipment	59 L
Cylinder Height	875 ± 1 mm
Cylinder Diameter	320 ± 2 mm
Cylinder Neck Thread	30 x 1.5
Valve Material	HPb59-1
Cylinder Material	HP265
Safety Valve	22-28 bar
Approx. gross Weight	96 kg
Approx. Dimensions	1100 x 640 x 490 mm
Paint Finish	RAL 3000
Packaging Details	Individual cardboard box



BS EN1886
 KM 597953
 Mobile Fire Extinguishers

Issue Date: 24/09/2024

Information may change

HEADQUARTERS: KATHIANA AKROTIRIOU P.C. 73100 CHANIA, CRETE - GREECE, TEL.: +30 28210 63222, FAX :+30 28210 91644

ATHENS DISTRIBUTION CENTER: SHINEZA - ASPROPIRGOS, P.C. 19300, ATTICA - GREECE, TEL.: +30 210 4614006, FAX: +30 210 5595986

NORTH GREECE DISTRIBUTION CENTER: 8 ARKADIOU str. KALOCHORI - THESSALONIKI, P.C. 57009, TEL.: +30 2310 785668, FAX: +30 2310 574793

CENTRAL & EAST CRETE DISTRIBUTION CENTER: P¹ str. INDUSTRIAL ZONE OF HERAKLION - CRETE - GREECE, P.C. 71601, TEL/ FAX: +30 2810 333151

www.mobiakfire.com