

# Major Fall Protection Series

Color zinc palted hardware  
Lanyard with froged hook  
Opening size of hook: 52mm

## MH106



### Applications: Industry

- Size: Universal
- Weight: 1.5kg
- Standard: EN361/EN358
- Material: Webbing Polyester,  
Metal part steel

### Buckle:

Chest	Shoulder	Waist	Legs
	N/A		

### Description:

#### ATTACHMENTS:

1 Dorsal D-Ring for Fall Arrest and 2 Lateral D-Rings at the waist for Work Positioning.

All D-rings are forged, heat-treated, and tested for a static tensile strength of 22 kN for 3 minutes.

#### ADJUSTMENTS:

4 Adjustment Points located at the Chest, Waist, and Thighs to adjust strap length as needed.

Includes one set of quick-release buckle (male and female) at the chest, one set at the waist, and two sets at the thighs.

Each buckle provides a static tensile strength of 15 kN for 3 minutes.

#### WEBBING:

Made from 100% PES (Polyester) with a 45 mm width, offering a static tensile strength of 25 kN for 3 minutes.

#### CONVENIENCE:

Shoulder and thigh straps are differentiated by a dual colour scheme for easy identification.

#### ERGONOMICS & COMFORT:

Equipped with an EVA lumbar pad for back support and enhanced comfort during long working hours.

#### COMPLIANCE:

Conforms to EN 361:2002 and EN 358:2018 international safety standards.

### Attchments:

