Description : **Rubber insulating gloves**

CURRENT

Features & Benefits :
* Made with special grade natural rubber compounds for assured electrical protection
* Superior anatomical construction results in lower hand fatigue
* Higher flexibility for long duration wear comfort
* 100% QC Inspection
* Packed in opaque UV resistant bags and individual boxes for product protection
* Each glove is inspected/tested for electrical insulation
* Electrical tests are performed on premium grade test machine custom made in USA (NO81A1-D)
* Compliant to EN 60903:2003
* Manufactured on a purpose built production line
* Produced at an ISO 9001:2015/ISO 14001:2015 accredited facility
* Compliant to PPE Regulation (EU) 2016/425

Applications : For power companies (utilities), Electrical workshops, Insulation, Maintenance and Repairs involving High Voltage Equipment

Product Details :

Elastomer : Natural rubber

Thickness : 0.5 mm *[Note: In case of categories A,H,Z and R, on additional thickness of 0.60 mm may apply]*

Lining : Unlined chlorinated

Former : Plain smooth

Cuff type : Straight

Exterior : Chlorinated

Colours : Black, Red, Natural

Type/Category : Category A, C, Z

Proof test voltage AC : 2500 V

Max. use voltage AC : 500 V

Physical Dimensions :

Size	Palm	Wrist	Cuff	Length
8	206	206	379	360
8 1/2	217	217	379	360
9	227	227	392	360
9 1/2	243	243	395	360
10	251	251	396	360
10 1/2	266	266	403	360
11	282	282	405	360

Internal circumference in mm,+/- 15 Tolerance +/- 15 mm

Physical Properties :

Tensile strength	16.0 MPa (min)	Tension set	15% (max)
Elongation at break	600% (min)		

Arc Flash Protection (Assessed according to EN 61482-1-2): APC 1

400 Deans Road Colombo 10 Sri Lanka